


Product Specification

10/100M Unmanaged Industrial Ethernet Switches (FLD-S-1F2F-I)

| Introduction | Image |
|--|--|
| <p><i>This industrial media converter FLD-S-1F2F-I is specially designed for industrial application, which provides fast and stable media conversion between 10/100BaseTX and 100BaseFX. It also meets the requirements of long distance, high speed, and wide broadcast.</i></p> <p><i>With wide range operation temperature, alloy aluminum shell and other excellent industrial-grade design against vibration and shock, it could keep your industrial automation applications running continuously in different harsh environments.</i></p> |  <p>CE FCC RoHS</p> |

| Features & Benefits |
|--|
| ❖ 2 10/100Base-T(X) ports and 1 100Base-FX port |
| ❖ -40°C-85°C operating temperature range |
| ❖ Super lightning protection, IP40 protection |
| ❖ Excellent heat elimination without cooling fan |

| Physical Characteristics |
|---|
| ❖ Housing: Aluminum Alloy material with IP40 Protection |
| ❖ Dimension: 138mm(L) X 112mm(W) X 42mm(H) |
| ❖ Weight: 480g |
| ❖ Installation: Din-Rail mounting, Wall mounting |

Switch Properties

- ❖ MAC Table Size: 2K
- ❖ Packet Buffer Size: 1M bit
- ❖ Processing Type: Store and Forward
- ❖ Exchange Properties: 148800pps (100M)

Interfaces

- ❖ 1 100Base-FX port (SC/ST/FC/LC connectors optional)
- ❖ 2 RJ45 Ports: 10/100Base-T(X) auto negotiation

Power

- ❖ Input Voltage: 24V DC(18-36VDC) Redundant dual inputs
- ❖ Input Current: <0.5A @24VDC
- ❖ Overload Current Protection: Present
- ❖ Reverse Polarity Protection: Present
- ❖ Redundant Protection: Present

Environmental Limits

- ❖ Operating Temperature: -40°C-85°C
- ❖ Storage Temperature: -40°C-85°C
- ❖ Ambient Relative Humidity: 5%-95% (non-condensing)

Standards

- ❖ EMS:
 - EN61000-4-2 (ESD), Level 3
 - EN61000-4-3 (RS), Level 3
 - EN61000-4-4 (EFT), Level 3
 - EN61000-4-5 (Surge), Level 3
 - IEC61000-4-8(100A/m), Level 3
 - IEC61000-4-11, Level 3
- ❖ Shock: IEC 60068-2-27
- ❖ Free Fall: IEC 60068-2-32

FIBERLAND

Fiber Optic & Networking Products

Let's create a pure fiberland for human beings

| | |
|---|--|
| ❖ | Vibration: IEC 60068-2-6 |
| ❖ | EMI: FCC CFR47 Part 15, EN55022/CISPR22, Class A |
| ❖ | Industry: IEC61000-6-2 |
| ❖ | Rail: EN50155, EN50121-4 |
| ❖ | Traffic: NEMA TS-2 |

Warranty

5 years

Contact :

| | |
|---------|---|
| Address | 6 th floor ,building 8,Zhongxing industrial zone,Nanshan district,Shenzhen,P.R.China |
| Zip | 518000 |
| Website | www.fiberlandtec.com |
| Email | sales@fiberlandtec.com |